


# Capacity Chart



		Thickness in inches																
		1.25	1.35	1.5	1.75	2	2.36	2.5	2.75	3	3.15	3.5	4	4.15	4.5	5		
Width in inches	2	1,730	2,069	2,703	3,421	4,223												50
	2.36	2,076	2,483	3,243	4,105	5,068	7,298											60
	3.15	2,768	3,311	4,325	5,473	6,757	9,730	11,420	13,244	15,204	17,299							80
	4	3,460	4,139	5,406	6,842	8,447	12,163	14,275	16,555	19,005	21,623	27,367	33,786					100
	4.75	4,152	4,967	6,487	8,210	10,136	14,596	17,130	19,866	22,806	25,948	32,840	40,543	44,699	53,619			120
	5	4,325	5,174	6,757	8,552	10,558	15,204	17,843	20,694	23,756	27,029	34,209	42,233	46,562	55,853	65,989		125
	5.15	4,498	5,380	7,028	8,894	10,981	15,812	18,557	21,522	24,706	28,110	35,577	43,922	48,424	58,087	68,628		130
	6	5,190	6,208	8,109	10,263	12,670	18,245	21,412	24,833	28,507	32,435	41,050	50,679	55,874	67,023	79,186		150
	7	6,227	7,450	9,730	12,315	15,204	21,893	25,694	29,799	34,209	38,922	49,260	60,815	67,049	80,428	95,024		180
	8	6,919	8,278	10,812	13,683	16,893	24,326	28,549	33,111	38,010	43,246	54,734	67,572	74,499	89,365	105,582		200
	10	8,649	10,347	13,514	17,104	21,116	30,408	35,687	41,388	47,512	54,058	68,417	84,466	93,123	111,706	131,977		250
	10.75	9,341	11,175	14,596	18,473	22,806	32,840	38,542	44,699	51,313	58,383	73,890	91,223	100,573	120,642	142,536		270
	11	9,687	11,589	15,136	19,157	23,650	34,057	39,969	46,355	53,213	60,545	76,627	94,601	104,298	125,110	147,815		280
	12	10,379	12,416	16,217	20,525	25,340	36,489	42,824	49,666	57,014	64,870	82,101	101,359	111,748	134,047	158,373		300
	13.75	12,109	14,486	18,920	23,946	29,563	42,571	49,961	57,943	66,517	75,681	118,252	118,252	130,373	156,388	184,768		350
	15.75	13,839	16,555	21,623	27,367	33,786	48,652	57,099	66,221	76,019	86,493	109,467	135,145	148,997	178,729	211,164		400
17.7	15,569	18,625	24,326	30,788	38,010	54,734	64,236	74,499	85,521	97,304	123,151	152,038	167,622	201,070	237,559		450	
20	17,299	20,694	27,029	34,209	42,233	60,815	71,373	82,776	95,024	108,116	136,834	168,931	186,247	223,411	263,955		500	
		32	35	40	45	50	60	65	70	75	80	90	100	105	115	125		
		Thickness in mm																

 = In-stock section sizes for quick delivery.

Capacity per pair in lbs. at 24" load center.

For other section sizes and load center details, please contact us.

Contact us at:  
 803-980-6800  
[sales@msiforksinc.com](mailto:sales@msiforksinc.com)  
 For more information:  
[www.msiforksinc.com](http://www.msiforksinc.com)